



BORMA WACHS[®]

Wood Professional Cosmetics



Technical Data Sheet

00 del 20.10.2012

PARQUET OIL

DESCRIPTION:

Natural oil based treatment, reinforced with high quality resins, for the finishing of wood floors, with the application of one or two coatings. Suitable for soft and hard timbers, in particular for adsorbent and porous woods. Can be used also for the varnishing of doors, window frames, skirtings and other wooden objects. Only for interiors. Formaldehyde free.

PHYSICAL – CHEMICAL CHARACTERISTICS:

Form:	liquid
Colour:	colourless
Odour:	typical
Dilution:	ready for use. In case it can be diluted up to 15% with Solvoil 04 or Solvoil 06
Application:	by brush, by roll or by soft cotton cloth
Yield:	80-100 ml/m ² per coat, depending on the application technique and on the timber absorbency
Drying time:	6 - 8 hours, depending on the thickness of the coating and on timber absorbency
Over varnish:	12-18 hours
Usage temperature:	not lower than + 10°C
Storage temperature:	not lower than + 5°C, keep from freezing
Tools cleaning:	white spirit
Safety instructions:	flammable

HOW TO USE:

Preparation of the parquet floor

Sand the surface to obtain a smooth surface, clean and free from oils, grease, waxes, silicon and old varnishes. Fill the slits and the superficial irregularities with HOLZMASSELÖSUNG (Binding resin for the individual preparation of wood filler). A final sanding with abrasive paper 150-180 grain brings a better final look to treatment. Before the application of the first coat aspirate all the dust residuals. The humidity rate of wood must be between 9 and 12%. Verify compatibility with unknown timbers (colouring, oil content, drying process inhibition, etc...). Some woods that are strongly coloured or of exotic origins (Lapacho, Ipe, Iroko, Mahogany-like etc...), can slow down the drying of PARQUET OIL. In these cases it is suggested to apply a very thin first coat of PARQUET OIL, and to ventilate well the room to favor the drying process.

Use

Stir well the content of the can before usage of the product. Use clean containers and tools. Apply according to the suggested consume rate. To obtain a regular drying apply even and not too thick layers. After sufficient hardening sand with abrasive paper or net, 220-240 grain and

dust off accurately before the application of a second coating. Sanding should be light but uniform. Not compatible with other basecoat and parquet varnishes.

Suggested varnishing cycles

For impregnation type oil finishings: apply directly on sanded and clean wood one or two coats with a soft cotton cloth, for a total consumption of 80 g/m² of product. In case, especially for low-porosity timbers, the first coat can be diluted with white spirit. For varnishing type finishings: application, directly on sanded and clean wood, of one or two coats by roll or brush, for a total consumption of 180 g/m².



BORMA WACHS[®]

Wood Professional Cosmetics

PACKAGE:

The product comes in 500 mL, Lt 1, Lt 5, Lt 15 and 750 mL (only for Coloroil System) sized cans. Available: opaque 10%, semiopaque 30%, semiglossy 60%, glossy 90%.

STORAGE:

Store in a cool, well ventilated place, keep the container closed when not in use. Keep away from heat, flames, sparks and other sources of ignition. Keep from freezing.

WARNING:

Sawdust, cotton cloth, paper and similar products soaked with liquid product and let in such condition may cause spontaneous combustion. Therefore, in case of presence of these materials for cleaning, ensure adequate air ventilation of the rooms in order to allow a rapid drying of the product or wet them with water before disposal.

Our data sheets are prepared on the basis of average performance of our tests. However, our technical advices are given in good faith but without any warranty. In fact different supports, conditions of application, industrial plants, dilutions are determinant for the final result, and are often beyond our control. The user must try the product to see if it is suitable for his needs. We will ensure the continuity of the chemical-physical characteristics.